

Technical Specs CX16

PRINTER FEATURES

- WYSIWYG printer display
- 1 or 2 line print capability
- Fonts - 5x5, 7x5, 16x10
- Rasters - standard & distance modes
- Text fields - up to 255 character
- Date field
- Time field
- Counter field
 - 8 digit increment or decrement
 - repeat
 - step
- Graphics
 - on screen editor
 - remote graphic import
 - character creation software
- Password enabled

PRINT ATTRIBUTES

- .07" - .59" (1.8mm - 15mm) print height
- 2mm - 40mm printhead throw distance
- 9 bold settings
- Inverse, reverse, mirror printing
- Orientation - vertical downward ± 85 degrees
- Recommended max print speeds-up to 350 fpm (single line 5x5 font)
- Encoder/photocell/continuous modes

PRINTER JET FUNCTIONS

- One button start/stop
- Automatic viscosity control
- Printer function diagnostics
- Printhead nozzle clearing functions

OTHER FEATURES

- Rugged stainless steel enclosure
- 3m printhead umbilical
- 5.5" LCD display with QWERTY keyboard
- Internal pump - No external air supply required
- Conditions: operating temperature: 41~104 °F (5~40 °C)
humidity range: 30-95% RH (non-condensing)
- Accessories - floor mount stand, photocell, encoder, stainless steel cabinet



PRIMARY APPLICATIONS

- Food & Beverage
- Electronic Components
- Household Products
- Cosmetics/Personal Care
- Pharmaceutical
- Chemical
- Automotive
- Wire & Cable
- Building Products
- Paper/Textiles
- Medical

Matthews Marking Products continually improves products. The right, therefore, is reserved to alter the design and/or specifications without giving prior notice.

Matthews Marking Products

Matthews
INTERNATIONAL

BRAND SOLUTIONS



Matthews Marking Products

6515 Penn Avenue, Pittsburgh, PA 15206
(412) 665-2500 • Fax: (412) 365-2042

Gamlestadsvägen 8, S-415 02 Göteborg, Sweden
(46) (31) 338 7900 • Fax: (46) (31) 84 51 17

Sold and Distributed Worldwide

© 2009 Matthews Marking Products